# E45

### the new range of lightweight amps

#### **E-Series** Power Amplifiers

These lightweight, switchmode amps have been designed to the same high standards of reliability and sound quality that our customers have come to expect of all MC2 Audio products.

Aimed at the touring market in particular, the **E45** at 2250W/channel into 4 ohms, built in a 2U chassis, has all the sonic qualities and reliability of the MC and T Series amplifiers, without the physical weight, making it an ideal choice for touring.

The switchmode power supply is capable of delivering high peaks without any perceptible bass 'sag' at very low distortion and is kept within its safe operating area by the new sophisticated MC2 'intelligent' limiter.

The **E Series** amplifiers will bring the well renowned MC2 sound quality and reliability to a wider range of users.

#### Features

- Digital power supply with large power reservoir giving extremely high peak power without any bass 'sag'.
- Proprietary designed progressive switching rail output.
- MC2 proprietary current driven output stages for ultra highdefinition sound.
- Full high frequency power the E Series amplifiers will deliver their power over the entire audio bandwidth.
- Lightweight aluminium construction.
- All new low distortion limiters with adjustable threshold points for extra speaker protection.
- Sophisticated power control system linked to both the limiter and the power supply, keeping the amplifier within its operating limits at all times.
- Power Reduction Circuit (PRC) controls on rear panel, linked to the limiter threshold which allow each channel to be independently set so that different loudspeakers can be connected to each channel with safety.
- Optional cross-over cards available. 24dB/Octave Linkwitz Riley.
- Soft start 'power on' with full in-rush protection.
- Full DC, short circuit and thermal protection, which automatically disconnects the outputs under a fault condition.
- Weighs around 11kg.
- 5-year warranty.





All  $MC^2$  products come with a full 5-year warranty.

#### www.mc2-audio.co.uk




## the new range of lightweight amps

#### E-Series Power Amplifiers

Т

	I	E45
	Output power (Watts RMS) per channel 8 ohms @ 1 kHz 4 ohms @ 1 kHz 2 ohms @ 1 kHz	1200 2250 3200
	Mono Bridged 8 ohms @ 1kHz 4 ohms @ 1kHz	4400 6400
	Power reduction control	-2dB/-4dB/-6dB
	THD @ rated power 4 ohms 1 kHz 20Hz-20 kHz	<0.008% <0.03%
	Input CMRR	>90dB
	Hum & Noise	-105dB
	Gain (Selectable)	+32dB/+26dB/+35.75dB
	Sensitivity (for rated output, 4 ohms)	+9.75dBu/+15.75dBu/+6dBu(1.5V)
	Damping Factor 1 kHz, 8 ohms	>400
	Frequency response	20Hz-20kHz - +0/-0.5dB
	Input impedance (actively balanced)	20k ohms
	Dimensions (mm) - 2U	88 x 482 x 428
	Weight	11kgs
	Power requirement	230 VAC @ 20 amps max 115 VAC @ 40 amps max
	Connectors Inputs Outputs	XLR 3 pin 4 pole SPEAKON
	Controls Front panel	2 x level controls 1 x power on/off switch
	Controls Rear panel	1 x Stereo/bridged mono switch 4 x PRC switches (2 per channel)
	Indicators	1 x power, 2 x limit, 2 x signal present, 2 x -3dB, 2 x power reduction control (PRC), 1 x auto protect, 1 x bridged.
	Opened B // Control B	A but of the second sec





Kingsgate Heathpark Honiton Devon ENGLAND EX14 1YG Tel: +44 (0)1404 44633 Fax: +44 (0)1404 44660

#### www.mc2-audio.co.uk